

340x185x80mm



4 CHANNEL AMPLIFIER

SPECIFICATIONS:

- RMS power: 4x125W @ 4 ohm
- RMS power: 4x250W @ 2 ohm
- Bridgeable power: 2x500W @ 4 ohm
- Frequency Response: 20Hz-20KHz
- S/N ratio: 95dB
- Input Sensitivity: 200mV-4V
- Switchable Bass Boost: 0dB-9dB
- X-over switch: FILL/HP/LP
- RCA line input and speaker output
- Three way protection: Short circuiting, thermal and overload protection.

1000W max



HD1000.4D

250W RMS X 4
@ 2 ohm
125W RMS X 4
@ 4 ohm
S/N : 95 dba

SPECIFICATIONS:

- RMS power: 4x125W @ 4 ohm
- RMS power: 4x250W @ 2 ohm
- Bridgeable power: 2x500W @ 4 ohm
- Frequency Response: 20Hz-20KHz
- S/N ratio: 95dB
- Input Sensitivity: 200mV-4V
- Switchable Bass Boost: 0dB-9dB
- X-over switch: FILL/HP/LP
- RCA line input and speaker output
- Three way protection: Short circuiting, thermal and overload protection.



4 CHANNEL AMPLIFIER

4 CHANNEL POWER AMPLIFIER




CONCEPT USA, INC.
WWW.CONCEPTBUY.COM

WARNING
Caution and Registration Mark

4 CHANNEL AMPLIFIER

HD1000.4D



4 CHANNEL POWER AMPLIFIER

CONCEPT

CONCEPT


4 CHANNEL POWER AMPLIFIER

250W RMS X 4
@ 2 ohm
125W RMS X 4
@ 4 ohm
S/N : 95 dba



HD1000.4D

1000W max



WARNING
Caution and Registration Mark

CONCEPT USA, INC.
WWW.CONCEPTBUY.COM



HD1000.4D
4 CHANNEL AMPLIFIER